



bizhub 451i

Black & White A3 multifunctional









Giving Shape to Ideas

CUSTOMER BENEFITS



Security

Secure network integration, data encryption, overwrite all data function, and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



Unicode fonts

OCR A and B fonts

Document converter pack

ThinPrint® client

Antivirus LK-116



2 CONNECTIVITY Fax board

х2

OR

OR)

Wireless LAN UK-221

USB I/F kit USB I/F kit

ID card reader

Mount kit MK-735

3 OTHERS

Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

1x Universal tray PC-116

2x Universal tray

Large capacity tray PC-417

Large capacity tray

Large capacity tray LU-207

Banner tray

5 MEDIA OUTPUT

Output tray OT-513

Off-line stapler

Attachment kit MK-607

Staple finisher FS-539

ınch kit for FS-539/SD

Staple finisher FS-540

Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

Post inserter for FS-540/SD PI-507

Job separator for FS-540/SD OR

LEGEND

Mandatory option

Option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES

































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

N							

LK-106 Barcode fonts	Supports native barcode printing		
LK-107 Unicode fonts	Supports native Unicode printing		
LK-108 OCR A and B fonts	Supports native OCR A and B font printing		
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A		
LK-111 ThinPrint® client	Print data compression for reduced network impact		
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incom-		
	ing and outgoing data		

CONNECTIVITY

FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

OTHERS

WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Kevboard holder	To place USB keyboard

MEDIA INPUT

Auto detects paper weight and type
500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²
2x 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²²
2,500 sheets, 8.5" x 11" / 52–256 g/m ²
1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m ²
3,000 sheets, 8.5" x 11" / 52–256 g/m²

MEDIA INPUT

LU-207 Large capacity tray	2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m²
MK-730 Banner tray	Multipage banner feeding
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
JS-508 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MK-607 Attachment kit	For FS-533 installation
PK-519 Punch kit for FS-533	2/3-hole punching, auto switching
FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3-hole punching; auto switching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100-sheet stapling; 20 sheets booklet finisher;
	2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3-hole punching; auto switching
RU-513 Relay unit	For FS-539/SD or FS-540/SD installation
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
ZU-609 Z-fold unit for FS-540/SD	Z-fold for 11" x 17" prints

20-sheet off-line stapling

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed 8.5" x11"	Up to 45 ppm
System speed 11" x 17"	Up to 22 ppm
Autoduplex speed 8.5" x11"	Up to 45 ppm
1st page out time 8.5" x11"	3.8 sec.
Warm-up time	Approx. 15 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 300 originals / 5.5" x 8.5" – 11" x 17" / 35–210 g/m² /
	Dual scan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" – 12" x 18" / customized paper sizes /
	banner paper max. 47.2" x 11.7"
Printable paper weight	52–300 g/m²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1 x 500 /3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m ²
	1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m 2
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m²
	2 x 500 / 5.5" x 8.5" - 11" x 17"/ 52-256 g/m ²
	12 500 / 0 5" 11" /52 255 / 2

1 x 2,500 / 8.5" x 11" /52-256 g/m²

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

 $52-256 \, g/m^2$

SYSTEM SPECIFICATIONS

FS-P04 Off-line stapler

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m²
	1 x 2,500/8.5" x 11" – 12" x 18" / custom sizes /
	52-256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60–300 g/m²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.1" x 5.5" - 12" x 18" / 52-256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Tri-fold	Max. 3 sheets
Tri-fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m^2)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Max. ² 200,000 pages
Toner lifetime	Black up to 24,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer)
Power consumption	110-120 V / 60 Hz, Less than 1.6 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

bizhub 451i Datasheet

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS
Operating systems	Windows 10 (32/64); Windows 11; Windows Server 2012;
	Windows Server 2012 R2; Windows Server 2016; Windows Server
	2019; Windows Server 2022; macOS 10.14 or later; Unix; Linux;
	Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS); Mopria (Android)
	optional: Wi-Fi Direct

SCANNER SPECIFICATIONS

Scan speed	Up to 140 ipm in simplex (mono)
	Up to 280 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation);
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Overwrite all data function; SSD self-encryption (AES 256)/
	Storage lock password; Confidential fax;
	Print user data encryption
Security function (optional)	Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Web Connection;
	Log Management Utility

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing,
- ambient temperature and humidity.

 Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to $change\ without\ notice.$
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



























YOUR OFFICE TECHNOLOGY EXPERTS

(631) 873 - 4560 info@drpsolutions.com www.drpsolutions.com 18 Commerce Drive, Suite 1 Hauppauge, NY 11788

 $^{^{\}rm 1}$ Warm-up time may vary depending on the operating environment and usage

 $^{^2\,} If \, the \, maximum \, volume \, is \, reached \, within \, a \, period \, of \, one \, year, \, then \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, be \, performed \, a \, maintenance \, cycle \, must \, a \, mus$